

Artikel Nr. Code No.	352305020700	352305030900	352305040000
Typ Type	2305-200-45	2305-250-72	2305-315-91
A	206	257	315
B	89	106	106
C	90	107	107
D H6	170	220	300
E	6	6	6
F	133,4	171,4	235
G	6xM12	6xM16	6xM20
H	20	28	31
J	20	25	25
K	57	86	108
L max.	M52x2	M80x2	M100x2
Max. Kolbenhub Max. Drawbar stroke	M		
O	24	28	28
P	45	72	91
R	73	100	122
Verzahnung Serration pitch	S		
T	3	3	3
U min.	5	5	4
U max.	25	28	27
max. Backenhu max. Jaw stroke	a		
b	20	20	20
c	37	54	54
d	M8x1	M12x1,5	M12x1,5
e	40	40	40
f	90	110	110
g	10	12	12
h	22	26	26
Backenausführungen Jaws type	F200	F250	F250
Max. Betätigungskraft [kN] Max. pulling force [kN]	45	60	60
Max. Gesamtspannkraft [kN] Max. clamping force [kN]	84	120	120
Max. Drehzahl [rpm] Max. speed [rpm]	5500	4500	3500
Massenträgheitsmoment [kgm ²] Moment of inertia [kgm ²]	0,04	0,31	1,9
Gewicht ohne Aufsatzbacken [kg] Weight without top jaws [kg]	20	35	54

