

Artikel Nr. Code No.	352404310600	352404320800	352404330000	352404340100	352404350300	352404360500	352404370700	352404380900	352404390000	
Typ Type	2404-135K	2404-160K	2404-200K	2404-250K	2404-315K	2404-400K	2404-500K	2404-630K	2404-800K	
A	135	169	210	254	315	400	500	630	800	
B	60	81	95	106	108	130	127	160	160	
C	59,5	79	93	104	106,5	126,5	127	158	158	
Aufnahme Mounting	D H6	110	140	170	220	220	300	380	520	520
E	4	6	6	6	6	6	6	8	8	
F	82,6	104,8	133,4	171,4	171,4	235	330,2	463,6	463,6	
G	3 x M10	6 x M10	6 x M12	6 x M16	6 x M16	6 x M20	6 x M24	6 x M24	6 x M24	
H	14,5	13,5	16,5	18	27	28	35	34	34	
K	45	60	66	94	108	140	182	230	284	
Max. Kolbenhub Max. drawbar stroke	M	10 (10/0)	16 (13/-3)	22,5 (16/-6,5)	27 (19,5/-7,5)	27 (23/-4)	34 (23/-11)	34,5 (16,8/-17,7)	44 (44/0)	44 (44/0)
P	34	45	52	75	91	120	160	200	255	
R	56	70	92	117	134	164	220	275	330	
S	1,5	2,6	2,6	2,6	0,6	0,5	3	4,1	4,1	
T	2	3	3	3	2,5	5	4	4	4	
U min.	-9,5	-5	-8	-18,5	-19	-23	-32,5	-22	-22	
U max.	0,5	11	14,5	8,5	8	11	2	22	22	
W	20,5	25,5	27,5	33	34	27	35	27	27	
Z	35	40	45	55	55	55	50	50	50	
X	M12	M16	M20	M24	M24	M24	M30	M30	M30	
Y	20	24	30	36	36	36	42	42	42	
Max. Backenhub Jaw stroke	a	2,7	3,5	5	6	6	7,85	8	10	10
Spitzverzahnung Serration	1,5x60°	1,5x60°	1,5x60°	1,5x60°	1,5x60°	1,5x60°	3.0x60°	3.0x60°	3.0x60°	
b min.	24	30,2	35,5	47,9	56,9	74,65	97	134	162	
b max.	26,8	33,7	40,5	53,9	62,9	82,5	105	144	172	
c min.	7	9	10,5	11,7	13,2	12,5	16	16	16	
c max.	20	25,5	33	41,7	60	51,5	86	116	166	
d	M8	M10	M12	M12	M16	M20	M20	M20	M20	
e	14	20	25	30	30	43	43	43	43	
f	40,5	51	64,5	73	94	115	143,5	170	225	
g H7	10	12	14	16	21	25,5	25	25	25	
h	25	38	40	45	52	60	60	70	70	
j	-	-	-	-	-	-	14	22	22	
k	-	-	-	-	-	-	23	37	37	
m	-	-	-	-	-	-	10	16	16	
n	-	-	-	-	-	-	21	35	35	
p	-	-	-	-	-	-	87	100	160	
Max. Betätigungskraft [kN] Max. pulling force [kN]	17,5	22	34	43	56	71	90	100	100	
Max. Gesamtspannkraft [kN] Max. clamping force [kN]	36	57	86	111	144	180	200	200	200	
Max. Drehzahl [U/min] Max. speed [rpm]	7.000	6.000	5.000	4.200	3.300	2.500	1.600	1.200	800	
Massenträgheitsmoment [kgm²] Moment of inertia [kgm²]	0,018	0,057	0,15	0,31	0,73	2,15	5	16	48	
Gewicht ohne Aufsatzbacken [kg] Weight without top jaws [kg]	6,3	13	23,5	39	61	119	168	322	539	

Alle Futter auf Anfrage auch in grösseren Ausführungen lieferbar! • Larger sizes available upon request!