

| Code No. | 7-779-0500 | 7-779-0600 | 7-779-0800 | 7-779-1000 | 7-779-1200 |
|---------------------------------------|------------|------------|----------------|----------------|------------|
| Type | 2605-135K | 2605-160K | 2605-200K | 2605-250K | 2605-315K |
| A [mm] | 135 | 169 | 210 | 254 | 315 |
| B [mm] | 60 | 81 | 95 | 106 | 108 |
| C [mm] | 59.5 | 79 | 93 | 104 | 106.5 |
| Mounting D H6 [mm] | 110 | 140 | 170 | 220 | 220 |
| E [mm] | 4 | 6 | 6 | 6 | 6 |
| F [mm] | 82.6 | 104.8 | 133.4 | 171.4 | 171.4 |
| G [mm] | 4 x M10 | 4 x M10 | 4 x M12 | 4 x M16 | 4 x M16 |
| H [mm] | 14.5 | 13.5 | 16.5 | 18 | 27 |
| K [mm] | 45 | 60 | 66 | 94 | 108 |
| Max. drawbar stroke M [mm] | 10 (10/0) | 16 (13/-3) | 22.5 (16/-6.5) | 27 (19.5/-7.5) | 27 (23/-4) |
| P [mm] | 34 | 45 | 52 | 75 | 91 |
| R [mm] | 56 | 76 | 92 | 117 | 134 |
| S [mm] | 1.5 | 2.6 | 2.6 | 2.6 | 0.6 |
| T [mm] | 2 | 3 | 3 | 3 | 2.5 |
| U min. [mm] | -9.5 | -5 | -8 | -18.5 | -19 |
| U max. [mm] | 0.5 | 11 | 14.5 | 8.5 | 8 |
| W [mm] | 20.5 | 25.5 | 27.5 | 33 | 34 |
| Z [mm] | 35 | 40 | 45 | 55 | 55 |
| X [mm] | M12 | M16 | M20 | M24 | M24 |
| Y [mm] | 20 | 24 | 30 | 36 | 36 |
| Jaw stroke a [mm] | 2.7 | 3.5 | 5 | 6 | 6 |
| Serration [mm] | 1.5x60° | 1.5x60° | 1.5x60° | 1.5x60° | 1.5x60° |
| b min. [mm] | 24 | 30.2 | 35.5 | 47.9 | 56.9 |
| b max. [mm] | 26.8 | 33.7 | 40.5 | 53.9 | 62.9 |
| c min. [mm] | 7 | 9 | 10.5 | 11.7 | 13.2 |
| c max. [mm] | 20 | 25.5 | 33 | 41.7 | 60 |
| d [mm] | M8 | M10 | M12 | M12 | M16 |
| e [mm] | 14 | 20 | 25 | 30 | 30 |
| f [mm] | 40.5 | 51 | 64.5 | 73 | 94 |
| g H7 [mm] | 10 | 12 | 14 | 16 | 21 |
| h [mm] | 25 | 38 | 40 | 45 | 52 |
| Max. pulling force [kN] | 17.5 | 22 | 34 | 43 | 56 |
| Max. clamping force [kN] | 36 | 57 | 86 | 111 | 144 |
| Max. speed [rpm] | 6,000 | 5,000 | 4,300 | 3,600 | 2,800 |
| Moment of inertia [kgm ²] | 0.014 | 0.047 | 0.133 | 0.315 | 0.779 |
| Weight without top jaws [lbs] | 12.79 | 26.46 | 48.50 | 78.26 | 126.77 |

Larger sizes available upon request!