

1

2

3

4


5

6




T-NUTS • SINGLE OR DOUBLE CONFIGURATION

Version I



Version II



Ø 135 - 800 mm

Code No.	Version	A	B	C	F	G	H h6	Screws*	Weight	BISON Chuck Type
1 pc		[mm]							[lbs]	
7-789-905	II	15.0	26.0	15.0	14	5.5	10.0	M8x16	0.04	2104-135K, 2105-135-34K 2405-135K, 2405-135-34K 2605-135K, 2605-135-34K
7-789-906S	II	17.5	36.0	18.5	20	7.5	12.0	M10x20	0.09	2105-160K, 2105-160-45K 2405-160K, 2405-160-45K 2605-160K, 2605-160-45K
7-789-906	II	17.5	34	16.0	18	7.5	12	M10x20	0.09	2409-160-46
7-789-908S	II	23	42	21.5	24	9.5	17.0	M12x25	0.22	2104-160, 2105-160-45 2404-160, 2405-160-45 2604-160, 2605-160-45 2409-200-66
7-789-908	II	20.5	46.5	20.5	25	8.5	14.0	M12x25	0.20	2104-200K, 2105-200-52K 2404-200K, 2405-200-52K 2604-200K, 2605-200-52K
7-789-910S	I	23	19	21.5	-	9.0	17.0	M12x25	0.07	2104-200, 2105-200-52 2404-200, 2405-200-52 2604-200, 2605-200-52 2409-250-91 2409-315-91 2488-200
7-789-910	II	22.5	51.0	21.5	30	8.5	16.0	M12x30	0.26	2104-250, 2105-250-75K 2404-250, 2405-250-75K 2604-250, 2605-250-75K
7-795-912	I	27	24	25.5	-	10.5	21.0	M16x30	0.11	2104-250, 2105-250-75 2404-250, 2405-250-75 2604-250, 2605-250-75 2488-315
7-795-912S	II	29.0	55.5	27.0	30	10.5	21.0	M16x30	0.46	2104-315K, 2105-315-91K 2404-315K, 2405-315-91K 2605-315K, 2605-315-91K
7-795-912	I	27	24	25.5	-	10.5	21.0	M16x30	0.11	2104-315, 2105-315-91 2404-315, 2405-315-91 2604-315, 2605-315-91
7-789-916	II	34.0	80.0	31.0	43	12.0	25.5	M20x40	0.84	2404-400K, 2405-400-120K
7-789-920	I	34	30	29.0	-	12.0	25.5	M20x40	0.20	2404-400, 2405-400-120
7-789-920S	I	34	30	29.0	-	12.0	25.0	M20x40	0.20	2404-500K, 2405-500-160K 2404-630K, 2405-630-200K 2404-800K, 2405-800-255K
7-789-920	I	34	30	29.0	-	12.0	25.5	M20x40	0.20	2404-500, 2405-500-160 2404-630, 2405-630-200 2404-800, 2405-800-255

Screws are included in delivery

WT